



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup>:
A61F 13/15

(11) International Publication Number:

WO 99/53878

**A1** 

(43) International Publication Date:

28 October 1999 (28.10.99)

(21) International Application Number:

PCT/US98/08205

(22) International Filing Date:

23 April 1998 (23.04.98)

(71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): MIYAMOTO, Kouichi [JP/JP]; Hakkouda Field #305, 7-5-14, Sumiyoshimiyamachi, Higashinada-ku, Kobe 658-0000 (JP). HEKI, Yukio [JP/JP]; 3-1-8-3-605, Koyo-cho Naka, Higashinada-ku, Kobe 658-0032 (JP). SUGITA, Masataka [JP/JP]; 6-1-608, Satsukigaoka Minami, Suita-shi, Osaka 565-0832 (JP).
- (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


## Published


With international search report.

(54) Title: DISPOSABLE ABSORBENT ARTICLE HAVING REINFORCED EAR PANELS

## (57) Abstract

Disclosed is an absorbent article having a longitudinal centerline and a lateral centerline, comprising; (a) a containment assembly having a rear waist region, a crotch region, a front waist region, a pair of longitudinal edges, a body facing surface and a garment facing surface opposite to the body facing surface, the containment assembly comprising a topsheet, a backsheet joined to the topsheet, an absorbent core positioned between the topsheet and the backsheet, and a pair of barrier leg cuffs having a proximal edge and a distal edge and being positioned adjacent to the longitudinal edges of the containment assembly; (b) a pair of rear ear panels extending laterally outwardly from the proximal edges of the barrier leg cuff in the rear waist region; (c) a pair of front ear panels extending laterally outwardly from the proximal edges of the barrier leg cuff in the front waist region; and (d) a reinforcement nonwoven joined to at least one of either the rear ear panels or the front ear panels, the reinforcement nonwoven not substantially overlapping the containment assembly.





b